

## TASK RANGE

HIGH BACK	
LY30	non tilt seat
LY35	tilt seat
LY36	3 paddle mech



LY30 shown



MEDIUM BACK	
LY20	non tilt seat
LY25	tilt seat
LY26	3 paddle mech



LY20 shown

MEDIUM / HIGH BACK WITH ARMS		
LY20A14	LY30A14	non tilt seat
LY25A14	LY35A14	tilt seat
LY26A14	LY36A14	3 paddle mech



LY20A14 shown



A5 Height adjustable arm

DRAFTING	
LY20D3	non tilt seat
LY26D3	3 paddle mech



LY20D3 shown



Approved Supplier  
SCCB Contract No. 1006  
20/10/2009 - 8/02/2013



Not all models have AFRDI certification. AFRDI certifies for select models available upon request.

DIMENSIONS	Back Size	Seat Size	Height
	High 470 W x 525 H Medium 430 W x 440 H	500 W x 460 D	Typist / Clerical 450 - 580 Drafting standard 560 - 760 Drafting high lift 630 - 890
OPTIONS	Option codes must be placed in alphabetical order after chair code.	A14 - Standard loop arms A5 - Height adjustable arms B1 - Polished aluminium base C1 - Brake castors (carpet floors) C2 - Brake castors (hard floors)	C5 - Glides D1 - Aluminium footring /Standard drafting D2 - Aluminium footring /High lift drafting D3 - Black plastic footring /Standard drafting D4 - Black plastic footring /High lift drafting
		E - Ergosit seat cushion M2 - Ratchet mechanism S5 - Large seat (515W x 480D) S6 - Extra large seat (560W x 500D) S5 - Slide seat option	

# OPTIONS

## TASK RANGE

Option codes must be placed in alphabetical order after chair code.



A5  
Height adjustable arm



A14  
Loop arm



B1  
Polished aluminium



C1  
Brake castors



C2  
Brake castors




C5  
Glides



D1 & D2  
Aluminium footring



D3 & D4  
Black plastic footring



E  
Ergositt seat cushion



M2  
Ratchet mechanism



S2  
Small seat (500W x 460D)



S6  
Large seat (560W x 500D)



### SLIDE SEAT INSTRUCTIONS

The Slide Seat mechanism allows the seat to slide forward increasing the seat depth by 50mm. It offers 5 locking positions.

As depth between the back and seat increases it allows larger people more comfort.

To operate simply lift the handle and slide the seat forward or backward to adjust into a one of the 5 locking positions. The mechanism should find each locking position without any force necessary.

